

TV Test Transmitter SFM

Order form "TV standards"

Customer: _____

Order No.: _____ Pos.: _____

SFM Basic Unit 2007.9106.10 / 50

SFM-B6 vision modulator (2008.0160.10)		
☐ A	VSB filter characteristic	
group delay define in SFM-B7		
SFM-B7 multi standard 1 (2008.0248.02)		
☐ ☐	VSB filter characteristic	
☐ ☐ ☐	group delay precorrection	
SFM-B7 multi standard 2 (2008.0248.02)		
☐ ☐	VSB filter characteristic	
☐ ☐ ☐	group delay precorrection	

Option: multi standard cassette 2 (2008.0248.10)

Vestigial sideband filter characteristic (parts sets SFM-T):

"A": Std. B/G/I1 (38.9 MHz) "C": Std. D/K (38.9 MHz) "E": Std. M, N (45.75 MHz)
 "B": Std. I (38.9 MHz) "D": Std. L/L', K1 (32.7 MHz) (*)

(*) SFM-B9 required for Std. L/L'

Please fill in identification character "A" - "E" according to the required VSB characteristic.

Group delay precorrection (adjustment):

"1": Std. B/G general	"5": Std. D/K OIRT	"12": Std. D/K CSFR
"2": Std. B/G Sweden	"6": Std. K1	" - ": Std. L/L' is flat
"3": Std. B/G Australia	"7": Std. M, N FCC	" - ": Std. I, I1 is flat
"4": Std. D/K CCIR	"8...11": reserved	

Please fill in identification number "1" - "12" according to the required group delay characteristic matching with the chosen VSB characteristic.